

Adjusted by:

E-mail:

Adjusted for:

Tel:

Date:

Total weight (g):

The weight changes based on the choices made below.

S3 Swing has divided, swing away leg support and an adjustable rear axle in carbon fibre. To find a balance that suits you the rear axle can be adjusted into different positions. Note desired measure at "Settings". S3 Swing has a seat height of 45cm in front and 43 cm at the rear, without cushion. To adjust the seat height you can chose other rearwheel sizes or a raising Kit with suitable castor fork from the List of options.
Max userweight: 100 kg for seat width 33-42 and 150kg for seat width 45-50 cm.

Save the guide to the "desktop" and open it with [Adobe Reader](#), for best function Design your wheelchair by clicking in the circles in this guide. Blue, underlined text is clickable to [show info](#) or image. **BB** = seatwidth, **HH**= backrest height

Original design

Alternative options

Other options

[info](#)

1) Chassis colour

- Black - Anodic Black
- Clear

- Optional colour - A higher price and longer delivery time for optional colour

[Optional colour](#) _____



2) Seat width (BB) [art.no.](#)

- 36 cm
- 39 cm
- 42 cm
- 45 cm
- 50 cm
- Clear

Art.no include: chassis, seat, backrest lock



3) Back rest

- S3 523BBHH
- Clear

Height (HH)

- 20 cm
- 25 cm
- 30 cm
- 35 cm
- 40 cm
- 45 cm
- Clear

- Tapered 525BBHH
- Curved back 524BBHH

[Info](#)

- Other back rest

[List of options](#) art. _____



4) Rear axle

- Carbon standard 33023BB
- Clear

- Carbon +15 mm 33023BC*

* seat width **BB** +1

Use this rear axle when choosing arm support at Accessories and/or increased seat height

- Other rear axle or seat height

[Increase seat height](#)

[List of options](#) art. _____



5) Castor and fork

- 120 mm 2100070 (x2 / wheelchair)
- Clear

- 90 mm 2100090 x2
- 150 mm 2100050 x2



6) Footrest

- Swing S3 cpl pair [article number](#)
- Clear

- Foot plate large, extended 80mm_forward [article number](#)

- Extended tubes 40 mm [article number](#)
- Heel straps for footplates [article number](#)



7) Brake

- Brake S3 4630000
- Clear



8) Rear wheel - without pushrim

- 24" Standard [art.no.](#)
- Clear

- 22" Standard
- 25" Spinergy X black spokes
- 26" Spinergy X black spokes

[Rear wheel sizes](#)

- Other rear wheel

[List of options](#) art. _____

Tire - choose tire

- Schwalbe Right Run 24", 25", 26"
- Standard
- Clear

- Rugged 24"
- Schwalbe Marathon Plus 24", 25"

- PU 24" (massive)



9) Pushrim

- Titanium 190DD11 (x2 / wheelchair)
- Clear **DD** = Wheel diameter

- Paragrip 19051DDBT x2
- Tetragrip 19052DDBTx2

- Maxgrip (contains latex) 1903060 x2
- Aluminum 190DD30 x2

Accessories



Side guard S3

- [Side guard S3](#) [Video](#)
[article number](#)
- Clear



Arm support

- [Arm support S3](#) [Video](#)
[article number](#)



Side guard U2 light

- [Side guard U2 light](#)
[article number](#)



Push handles

- [Height adjustable S3](#) [Video](#)
4252060
- Clear



Push handle Foldable

- [Foldable S3](#) [Video](#)
4245000



Push bar

- [Push bar S3](#)
42400BB



Anti-tip

- [Anti-tip](#) std seat height
4353000 [Video](#)
- [Other seat height](#)



Cushion

- [2,5 cm](#)
- 47200BB
- [5 cm](#)
- 47500BB
- Clear



Spoke protectors

- [24" Panthera logo](#)
4500000
- [24" without logo](#)
4500011
- Clear



Other

- [Tube protection](#) _____ pcs
9900251 (x3/wheelchair)
- [Crutch holder](#) _____ pcs
9900300 (x2/crutch)
- [Backrest wedge](#) _____ pcs
4710012

Set-up adjustments



Backrest angle

Note measure (A) for desired back rest angle.
14-28 mm. Standard=18 mm
A= _____ mm



Rear axle adjustment

Note measure (A) for desired balance.
Standard=40 mm
A= _____ mm



Footrest height

Note measure (A) and (B) for the footrest.
A= _____ mm B= _____ mm



Transportation marking

- YES do mark the wheelchair with attachment points for transport in disabled service vehicle.

NOTE! See [manual](#) for more information.

Extra